



## AFLEX 3009

### Flexible Current Probes (1200A) for PROVA 6830A

#### Features:

- Flexible current probes (3pcs. per set) for **PROVA 6830A** only.
- Range selection: **Manual** (120A, 1200A).

#### Electrical Specifications:

Please refer to **PROVA 6830A+AFLEX 3007**.

#### General Specifications:

**(3pcs. per set)**

Probe Length:	3009-18	18 in / 460 mm
Minimum Bending Diameter:		35mm
Connector Diameter:		23mm
Cable Diameter:		14mm
Cable Length from Probe to Box:		1700mm
Cable Length from Box to Output:		1700mm
Range selection:		Manual (120A, 1200A)
Dimension (Box):		130mm(L) x 80mm(W)x 43mm(H) 5.1"(L) x 3.1"(W) x 1.7"(H)
Battery:		Powered by power analyzer
Operating Temperature:		-10°C to 85°C
Operating Humidity:		15% to 85% RH
Altitude:		up to 2000M
Storage Temperature:		-20°C to 85°C
Storage Humidity:		15% to 85% RH
Weight:		390g per pc., 3pcs. per set

### PROVA INSTRUMENTS INC.

**Add:** 6F-2, No. 129, Lane 235, Pao-Chiao Road, Shin-Tien District,  
New Taipei City 23145, TAIWAN

**Tel:** 886-2-89191255

**E-mail:** [prova@ms3.hinet.net](mailto:prova@ms3.hinet.net)

**Fax:** 886-2-89191489

**Website:** [www.prova.com.tw](http://www.prova.com.tw)